

# IOKA Natural Timber Exterior Protector Oil

## OVERVIEW

IOKA Timber Oil is a penetrating, non-filming, natural plant chemistry timber protector, made in New Zealand. Designed for timber cladding, IOKA Timber Oil is suitable for application on all exterior wood, decks, outdoor furniture and can also be specified for interior finishing.

IOKA Timber Oil is a high quality deeply penetrating oil that utilises a stable fungicide to help protect and directly reduce the effect of mould and decay. It is formulated from nature's finest ingredients including tung oil, plant waxes, micro earthen pigments, eucalyptus oil and pharmaceutically refined solvent.

Available in twelve colours, IOKA Timber Oil contains water repelling properties to reduce excessive warping, cupping and splitting and feed the timber as when it was a tree.

Sensibly maintained, IOKA Timber Oil will help resist exterior weathering over the years to come.

## COLOUR

Available in a range of rich UV stable, earthen clay pigments to help maintain and complement your timber's character. Base timber tone, seasoning, band sawn or dressed finish, will all influence the oil's application rate and the final colour.

Colours on dressed faced timber may require a further coat at 12 months, due to the reduced absorption rates of dressed timber compared to band sawn.

IOKA Timber Oil 'Clear' will silver and weather naturally as it is exposed to UV light. For ease of maintenance we recommend this for applications where a natural silvered timber look is required.

## PREPARATION

Ensure timber is clean, dry and free of sawdust, nails or metal filings. If accessible, apply one coat to rear side and end grain of timber cladding. This will help promote total protection.

## APPLICATION

Stir well prior and during – brush or spray apply. (for spraying – airless equipment with 18-20 thou. tip provides best delivery). Apply two even coats – 24 hrs apart. If your timber has been factory line coated before construction, then one sensible, liberal coat on the board face is all that is required. Remove any excess oil remaining above the surface within one hour of application.

# IOKA Natural Timber Exterior Protector Oil

---

## COVERAGE

---

|                   | <b>1ST COAT</b> | <b>2ND COAT</b> |
|-------------------|-----------------|-----------------|
| Dressed Hardwoods | 8-10 sqm/ltr    | 12-14 sqm/ltr.  |
| Dressed Softwoods | 4-6 sqm/ltr     | 6-8 sqm/ltr.    |
| Cedar             | 3-4 sqm/ltr     | 5-7 sqm/ltr     |

A band sawn finish will absorb approximately 25% more oil than above indicatives.

## MAINTENANCE

---

After noting weather/sun aspects, apply a third coat at 18 months. Thereafter an expected re-coat time is 5-7 years depending on sun aspect and general weather exposure.

## CLEANING OF IMPLEMENTS :

---

Immediately after use clean equipment with white spirits or mineral turps, followed by soap and water. (for best results use a plant based detergent)

## SAFETY INSTRUCTIONS :

---

Do not pour oil residue into the sewer. Let the remnants dry out and dispose with your domestic rubbish collection. Do not crumple soaked rags (otherwise spontaneous combustion may occur)

## INGREDIENTS:

---

Tung Nut Oil, Isoparafin L, Gum Rosin, Carnauba Wax, Candelilla Wax, Eucalyptus Oil, Lead free Driers, Acticide.